



CONTENTS

# CONTENTS

# (JUNE 2016)

# (pages 1-10)

# MATERIAL FLOW OPTIMIZATION THROUGH MODELLING AND SIMULATION IN THE SOFTWARE TOOL TX PLANT SIMULATION

Peter Trebuňa, Miriam Pekarčíková, Andrea Petríková, Radko Popovič, Marek Kliment

# (pages 11-15) MONTE CARLO SIMULATION FOR ANOVA Gabriela Ižaríková

# (pages 17-20) MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS

Sergey Ponomarev, Artem Bondarenko, Elena Averianova, Marina Spolohova

Acta Simulatio



Volume: 2 2016 Issue: 2 Pages: 1-10 ISSN 1339-9640

MATERIAL FLOW OPTIMIZATION THROUGH MODELLING AND SIMULATION IN THE SOFTWARE TOOL TX PLANT SIMULATION

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

Received: 26 Feb. 2016 Accepted: 17 July 2016

# MATERIAL FLOW OPTIMIZATION THROUGH MODELLING AND SIMULATION IN THE SOFTWARE TOOL TX PLANT SIMULATION

Peter Trebuňa

TU of Košice, Faculty of Mechanical Engineering, Institute of technology and management, Department of Industrial Engineering and Management, Nemcovej 32, 04 200 Košice, peter.trebuna@tuke.sk

## Miriam Pekarčíková

TU of Košice, Faculty of Mechanical Engineering, Institute of technology and management, Department of Industrial Engineering and Management, Nemcovej 32, 04 200 Košice, miriam.pekarcikova@tuke.sk

## Andrea Petríková

TU of Košice, Faculty of Mechanical Engineering, Institute of technology and management, Department of Industrial Engineering and Management, Nemcovej 32, 04 200 Košice, andrea.petrikova@tuke.sk

### Radko Popovič

TU of Košice, Faculty of Mechanical Engineering, Institute of technology and management, Department of Industrial Engineering and Management, Nemcovej 32, 04 200 Košice, radko.popovic@tuke.sk

## Marek Kliment

TU of Košice, Faculty of Mechanical Engineering, Institute of technology and management, Department of Industrial Engineering and Management, Nemcovej 32, 04 200 Košice, marek.kliment@tuke.sk

Keywords: modelling and simulation, optimization, efficiency, cost, return on investment

*Abstract:* The article is oriented on the optimization of material flow through modelling and simulation in the software tool Tx Plant Simulation. The company in which optimization was realized is engaged in production of plastic and aluminum windows and doors. The aim of optimization was to propose production disposition which would provide the production productivity increase, since company expands its activity portfolio also to foreign markets. Part of the proposal is evaluation and return on investment of the proposed production disposition, specifically, the calculation of economic efficiency of investments through indicators: net present value, index present value, discounted payback period, discounted economic value added DEVA. The estimated values of these characteristics are further used for the economic evaluation of investment costs and benefits of these proposals.

# **1** Introduction

The company which is the subject of the case study is a company engaged in the production and sale of plastic windows and doors. It focuses mainly on the Slovak market, but in recent years it began to work also with foreign countries. The main objective of the company is to deliver quality products at a reasonable price and in time. The products are made of quality materials and compliance with technological processes, allowing them to ensure high quality products with minimal complaints.

The company has one production hall, which produces plastic and aluminum windows and doors. The offices are in the hall. Warehouses are directly in the production hall. Great attention is paid to assembly work, since improper installation of the most common causes the reduction of product quality and comfort of use.

The company has one production factory (Fig.1), which produces plastic, and aluminum windows and doors. The offices are in the hall. Warehouses are directly by the production hall, but also inside of it (Fig.2). Materials storage works on electronic customer's orders, which are processed by software. This software is not connected with production. After that, process engineer create the technological procedure. Storekeeper orders the material which is necessary for processing the contract.

Company disposes with production hall, where plastic and aluminum windows and doors are produced. Parts of the production hall are also warehouses and offices (Fig. 1). is a plan view of the hall. There are shown the different workplaces, warehouses, locker rooms, and offices.

A flow chart elaborated in Tab. 1 shows the sequence of technological operations of the manufacturing process for the production of plastic windows. It is important for the analysis of material flow to monitor:

- individual transactions in the context of production activities in terms of type and time,
- handling activities and methods of transportation, storage,
- control quality and quantity,
- organizational provisions for the particular motion, waiting, idle time, etc.



Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment



Legend: 1. CNC saws, 2. belt hacksaw, 3. work desk with drill, 4. cutter, 5. drill, 6. welder double-barreled, 7. cutter, 8. work desk with neatening cutter, 9. work desk with drill, 10. saw on glazing bars, 11. roller track, 12. saw on metal, 13. cutter, 14. the singlepress, 15. saw on glazing bars, 16. workbench with neatening cutter, 17. workbench with drill, 18. tool cabinets, 19. warehouses, 20. dressing rooms, 21. Offices, 12. saw on metal Figure 1 Ground plan of the production hall of the company



Figure 2 Production hall and warehouses of the company



Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

			Table 1 Flow	v chart of wir	ıdow productio	n			
Num.	Type of			Symb	ol of operatio	ns			Time
	activity	•			X un/loading			D	[min]
		operation	transport	control	_	storage	packing	waiting	
1.	Sawing of plastic profiles								15
2.	Cutting of reinforcement								15
3.	Completion			A					25
4.	Milling								10
5.	Drilling								7
6.	Welding								22
7.	Machining of			λ					15
	corners								
8.	Bonding of								30
	gaskets								
9.	Montage of			$\triangleright$					45
	fitting								
10.	Cutting of								15
	glazing beads								
11.	Glazing								30
12.	Final testing								12
13.	storage and								-
	transportation								

Simulation time: 8:00:00.0000



Cumulated Statistics of the Parts which the Drain Deleted

Figure 3 Production hall of the company modelled in Tx Plant Simulation in 3D

~ 3 ~

Volume: 2 2016 Issue: 2 Pages: 1-10 ISSN 1339-9640

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment



Copyright © Acta Simulatio, www.actasimulatio.eu



Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

		Ta	ible 2 Time	portions of th	e workers in Tx I	Plant Simulation	
	Working	Setting-up	Repairing	Transporting	En-route to job	Waiting for Importers	Waiting for MUs Failed
Worker8	0.00%	0.00%	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%
Worker	0.00%	0.00%	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%
Worker1	59.57%	0.00%	0.00%	0.00%	0.01%	40.42%	0.00% 0.00%
Worker2	82.90%	0.00%	0.00%	0.00%	0.01%	17.09%	0.00% 0.00%
Worker4	97.07%	0.00%	0.00%	0.00%	0.01%	2.92%	0.00% 0.00%
Worker3	47.06%	0.00%	0.00%	0.10%	0.10%	52.74%	0.00% 0.00%
Worker6	90.18%	0.00%	0.00%	0.33%	0.30%	9.20%	0.00% 0.00%
Worker8	5.02%	0.00%	0.00%	0.00%	0.02%	94.96%	0.00% 0.00%
Worker5	50.42%	0.00%	0.00%	0.00%	1.09%	48.50%	0.00% 0.00%
Worker7	89.15%	0.00%	0.00%	0.00%	0.33%	10.52%	0.00% 0.00%

The result of the analysis of material flow of plastic windows in the company is concerned to the fact, that if a company wants to increase its productivity from about 30 windows per day to at least 80 windows per day, it will be necessary to optimize production disposition and propose a new production line, Fig.3 and Fig. 4 and Tab. 2. To increase productivity, factory needed to rationalize the material flow through the simulation program Tx Plant Simulation.

- Aim was to:
- eliminate unnecessary handling,
- increase production productivity,
- ensure proper working conditions and safety at work,
- optimize in-process handling and storage.



Legend: 1. STBAZ PVC 300 X-Slicers and machining center, 2. SE-VSM-CS-Vertical quadriceps welder, 3. FBS-2M-H - Semi screwdriver to screw the fitting components to the wing 4. Fixus D-Control and glazing unit, 5. ELAN OS- retaining wall, 6. Hacksaw, 7. cutter, 8. the single-press, 9. Saw on glazing bars, 10. Workbench with unique debarring cutter, 11. Work desk with a drill, 12. Tool cabinets

Figure 5 Production hall with the proposed production line

The proposed production line needs four employees to operate the machinery. It's lead to a reduction in the number of employees from the eight staff allocated to the production of plastic windows to 4. Fig. 5 shows the flow of materials between workplaces. Material flow of plastic windows is marked in red, material flow of aluminum products is marked in dashed line.

Optimization of the production process was elaborated with help of software support TX Plant Simulation, Fig. 6 and Fig. 7. It is a view of placement some particular workplaces, needs of workers' and views of material flow

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

in the form of Sankey diagram, which reflects the intensity of flow between the different workplaces.

With the investment in this range company will shorten the production process, reduce scrap, improve the quality of their products, and increase productivity. It will be able to expand into foreign markets, such as Poland, Czech Republic. Also reduce the number of production workers from 8 to 4, which will have the effect of reducing labour costs. The result is an increase of income.

### Simulation time: 8:00:00.0000

		Cumulate	ed Statistics	of t	he Parts wh	nich the Dra	ain Delet	ed	
Object	Name	Mean Life Time	Throughput	TPH	Production	Transport	Storage	Value added	Portion
vystup	hlinikove_okna	12:24.7130	47	6	98.97%	0.81%	0.22%	88.62%	
vystup	plastove okna	13:57.8330	37	5	97.32%	0.72%	1.97%	78.77%	



Figure 6 Production hall with the proposed production line in 3D



Figure 7 Production hall with the proposed production line

~ 6 ~



Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

Resource statistics as listed in Tab. 3, Tab.4 gives an overview of capacity utilization as well as downtimes of individual machines and equipment for the production of plastic and aluminum windows. It is a statistical summary of production during the course of an eight-hour work shift. Summary statistics indicate the number of pieces that have been produced and the time of production, transportation and storage expressed as a percentage.

ailed

	Τc	ible 3 Tim	e portions	of the worke	ers in Tx Plant	Simulation after opti	mization
	Working	Setting-up	Repairing	Transporting	En-route to job	Waiting for Importers	Waiting for MUs F
-4	12.36%	0.00%	0.00%	0.00%	1.40%	86.24%	0.00% 0

Vorker1	29.58%	0.00%	0.00%	0.00%	1.23%	69.19%	0.00% 0.00%
Vorker6	98.50%	0.00%	0.00%	0.00%	1.20%	0.30%	0.00% 0.00%
Vorker2	27.71%	0.00%	0.00%	0.00%	2.14%	70.15%	0.00% 0.00%

 $Table\ 4\ Resource\ statistic\ in\ Tx\ Plant\ Simulation\ after\ optimization\ Cumulated\ Statistics\ of\ the\ Parts\ which\ the\ Drain\ Deleted$ 

 Object Working Set-up Waiting Stopped Failed Paused Mean Life Time Mean Exit Time Total Throughput Throughput per Hour Throughput per Day

 vystup
 84.76%
 0.00%
 15.24%
 0.00%
 0.00%
 13:05.7301
 5:32.6095
 84
 10.5
 252

Part Types which the Drains Deleted

Object All Types hlinikove\_okna plastove\_okna vystup 84 47 37

Detailed Statistics of the Part Types Which the Drain Deleted

vystup Production					Transport					Storage									
4	Working	Set-up	Waiting	<b>Stopped Failed</b>	Paused	Sum	Working	Set-up	Waiting	Stopped Failed	Paused	Sum	Working	Set-up	Waiting	Stopped F	ailed P	aused	Sum
hlinikove_okna	88.62%	0.00%	10.35%	0.00% 0.00%	0.00% 9	8.97%	0.81%	0.00%	0.00%	0.00% 0.00%	0.00% 0	.81%	0.00%	0.00%	0.22%	0.00% 0	.00%	0.00%	0.22%
plastove_okna	78.77%	0.00%	18.54%	0.00% 0.00%	0.00% 9	7.32%	0.72%	0.00%	0.00%	0.00% 0.00%	0.00% 0	.72%	0.00%	0.00%	1.97%	0.00% 0	.00%	0.00%	1.97%

vystup		Life Time				Exit Time				Throughp	ut
	Mean Value	Standard Deviation	Minimum	Maximum	Mean Value	<b>Standard Deviation</b>	Minimum	Maximum	Total	Per Hour	Per Day
hlinikove_okna	12:24.7130	27.2623	12:19.1737	15:22.5978	10:00.1432	9.4462	9:31.7228	10:28.2772	47	5.875	141
plastove_okna	13:57.8330	2:45.1775	13:14.3832	29:52.7912	12:08.3832	56.1849	10:02.7682	14:13.9983	37	4.625	111

Portions of the States

Object	Working	Set-up	Waiting	Blocked	Powering up/down Failed	Stopped	Paused U	Inplanned	Portion
vstup_2	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
narezove_obrabacie_centrum	3.40%	0.00%	10.36%	86.24%	0.00% 0.00%	0.00%	0.00%	0.00%	
stvorhlava_zvaracka	11.25%	0.00%	2.74%	86.01%	0.00% 0.00%	0.00%	0.00%	0.00%	-
vstup_1	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
poloautomaticky_skrutovac	10.21%	0.00%	2.42%	87.37%	0.00% 0.00%	0.00%	0.00%	0.00%	
vystupna_kontrolna	17.50%	0.00%	82.50%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
pila_na_kov	8.96%	0.00%	0.90%	90.14%	0.00% 0.00%	0.00%	0.00%	0.00%	
freza	41.67%	0.00%	58.33%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
jednohlavovy_lis	8.13%	0.00%	91.88%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
pila_na_zasklievacie_listy	10.21%	0.00%	10.64%	79.15%	0.00% 0.00%	0.00%	0.00%	0.00%	
pracovny_stol_zacistovacia_freza	8.54%	0.00%	91.46%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
pracovny_stol_vrtacka	40.17%	0.00%	59.83%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
oporna_stena	0.00%	0.00%	2.30%	97.70%	0.00% 0.00%	0.00%	0.00%	0.00%	_
valcekova_trat	100.00%	0.00%	0.00%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
vystup	0.00%	0.00%	100.00%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	-
vstup_3	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
Buffer	0.00%	0.00%	100.00%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
hlinikove_okna	99.12%	0.00%	0.88%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
Buffer1	0.00%	0.00%	100.00%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
Buffer2	0.00%	0.00%	100.00%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
Source	0.00%	0.00%	0.00%	100.00%	0.00% 0.00%	0.00%	0.00%	0.00%	
pila_na_zasklievacie_listy_1	8.13%	0.00%	2.74%	89.13%	0.00% 0.00%	0.00%	0.00%	0.00%	
plastove_okna	79.16%	0.00%	20.84%	0.00%	0.00% 0.00%	0.00%	0.00%	0.00%	

Simulation time: 8:00:00.0000

		Cumulate	ed Statistics	of t	he Parts wh	ich the Dra	ain Delet	ed	
Object	Name	Mean Life Time	Throughput	TPH	Production	Transport	Storage	Value added	Portion
vystup	hlinikove_okna	12:24.7130	47	6	98.97%	0.81%	0.22%	88.62%	
vystup	plastove_okna	13:57.8330	37	5	97.32%	0.72%	1.97%	78.77%	

Acta Simulatio



# MATERIAL FLOW OPTIMIZATION THROUGH MODELLING AND SIMULATION IN THE SOFTWARE TOOL TX PLANT SIMULATION

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

# 2 Economic efficiency evaluation of the proposed production disposition,

The price of production line is  $320\ 000 \notin$ , costs associated with installation, shipping is  $2000 \notin$ . The company can invest 40% from the price, it represents 128 800  $\notin$ . The remaining 60%, which amounts to 193 200  $\notin$ , would have asked for a loan from the bank for six years, the other inputs data are in Tab. 5.

Table 5 Inputs date	a				
price of the production line	320 000 €				
costs related to installation,	2 000 €				
transportation					
own resources	128 800 €				
external resources	193 200 €				
time of the loan	6 years				
interest rate	6 %				
installment	the same height				
depreciation group	2				
required rate of return	11%				

increase in net working capital	o 1 000 €/for 6
	years
number of pieces per year	18 000 pieces
price	220 €/ pieces
WACC	11%

The calculation of labour costs:

- for 1 worker:
  - number of hours of one worker 1687,5 hours.
  - hourly wage is  $3,20 \in$
  - o annual costs for hourly wage is 5 400 €.
  - for 8 workers:
    - -8 hours for workers is 13 500 hours.
    - hourly wage is  $3,20 \in$ .
    - annual costs for hourly wage is  $43\ 200$  €.

Labour costs would be 21 600  $\in$ . In Tab. 6 there is composed of repayments for a period of six years.

Table 6 Repayment S	Schedule
---------------------	----------

Year	State of the loan	Installment of the loan	Payment of interest	Annuity
1.	193200,00	27697,66	11592,00	39289,66
2.	165502,34	29359,52	9930,14	39289,66
3.	136142,82	31121,09	8168,57	39289,66
4.	105021,73	32988,36	6301,30	39289,66
5.	72033,37	34967,66	4322,00	39289,66
6.	37065,72	37065,72	2223,94	39289,66
Σ		193200,00	42537,96	235737,96

After the completion of the repayment plan (with the same amount of total payments) payment will get the sum 39 289,66  $\in$ . The total loan amount is 235 737,96  $\in$ . Quantifying the expected costs and benefits:

Revenues: 3,960,000 € (unit price x volume) Cost:

- + direct materials: 2 340 000 € (130 €\*18 000 pieces)
- + direct salary: 21 600 € (6750 hrs.\*3.20 €)

+ indirect materials: 18 000 € (10 €\*18 000 pieces) + energy: 25 500 € (0.3 €/kWh\*85 000 kWh) Σ 2 405 100 €, the cost is 133.6 €/window.

Tab.7 contains calculations that are needed to determine the annual cash receipts, net present value, index, and present value discounted payback period.

Indicator	1	2	3	4	5	6
Revenue	3 960 000	3 960 000	3 960 000	3 960 000	3 960 000	3 960 000
-Costs	2 405 100	2 405 100	2 405 100	2 405 100	2 405 100	2 405 100
-Depreciation	53666,67	53666,67	53666,67	53666,67	53666,67	53666,67
Gross profit	1501233,33	1501233,33	1501233,33	1501233,33	1501233,33	1501233,33
-Income tax	285234,33	285234,33	285234,33	285234,33	285234,33	285234,33
(19%)						
Net profit	1215999	1215999	1215999	1215999	1215999,	1215999
+Depreciation	53666,67	53666,67	53666,67	53666,67	53666,67	53666,67
- Net working	1000,00	1000,00	1000,00	1000,00	1000,00	1000,00
capital						
Annual cash	1268665,67	1268665,67	1268665,67	1268665,67	1268665,67	1268665,67
income						
i=0,11	0,9009	0,8116	0,7319	0,6587	0,5935	0,5346
Discounted	1142940,90	1029649,06	928536,40	835670,08	752953,07	678228,67

Table 7 Calculations for net present value, index present value, discounted payback period





MATERIAL FLOW OPTIMIZATION THROUGH MODELLING AND SIMULATION IN THE SOFTWARE TOOL TX PLANT SIMULATION

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

payback period						
Cumulated DPP	1142940,90	2172589,96	3101126,36	3936796,43	4689749,51	5367978,17

Annual cash income of 1 268 665,67 €.

The net present value (1):

$$\check{CSH} = \sum PPn * \frac{1}{(1+i)^n} - KV \tag{1}$$

NPV = 5367978,17- 322 000 NPV = **5045978,17 €**- Investment is acceptable.

Index present value (2):

Indicator

Gross profit

Revenue

-Costs -Depreciation

$$ISH = \frac{\sum PPn * \frac{1}{(1+i)^n}}{KV}$$
(2)

$$ISH = \frac{5367978,17}{322000} = 16,67$$

IPV = **16,67** €-1 €the investment will bring € 16.67.

Discounted payback period (3):

$$DDN = \sum PPn * \frac{1}{\left(1+i\right)^n} = KV \qquad (3)$$

$$DDN = 0 + \frac{322000}{1142940,90} = 0,28$$

DPP = **0,28** year.

6

3 960 000 2 405 100

53666,67

1501233,33

5050158

Annual cash income reaches 1 268  $665,67 \in$ . Net present value is a positive value of 5 045 978,17 $\in$ , the investment is acceptable. Index of present value is  $16.67 \in$ , bringing one euro invested. Payback period is 0.28 years. By help of indicator DEVA/discounting the economic value added is determined whether the market value of the company will grow. The procedure of the calculation for DEVA is in Tab.8.

1	2	3	4	5
3 960 000	3 960 000	3 960 000	3 960 000	3 960 000
2 405 100	2 405 100	2 405 100	2 405 100	2 405 100
53666,67	53666,67	53666,67	53666,67	53666,67
1501233,33	1501233,33	1501233,33	1501233,33	1501233,33

Table 8 Calculations for DEVA

EBIT						
-Income tax	285234,33	285234,33	285234,33	285234,33	285234,33	285234,33
(19%)						
Net profit	1215999	1215999	1215999	1215999	1215999,	1215999
NOPAT						
С	322000	268333,33	214666,66	160999,99	107333,32	53666,65
C*WACC	35420	29516,6663	23613,3326	17709,9989	11806,6652	5903,3315
EVA	1180579	1186482,33	1192385,66	1198289,00	1204192,33	1210095,67
i=0,11	0,9009	0,8116	0,7319	0,6587	0,5935	0,5346
DEVA	1063583,62	962949,06	872707,07	789312,96	714688,15	646917,14
						Σ

DEVA is 5 050 158,00  $\in$ , which means that DEVA> 0 - the investment is acceptable, the market value of the company will grow.

From the optimization of production line of company, benefits are following:

- increasing the production of 30 windows of at least 80 windows per day, representing an impact of 166,6%;
- reducing the number of employees from 8 to 4, saving staff costs is 21 600 €,
- return on investment in the production of 80 windows per day is 0,28 years,
- one euro invested would give 16,67 €,
- · the company's market value will increase,

- speedier customer orders,
- possibility of involvement in demanding projects,
- penetration into foreign markets,
- increasing quality of product.

## Conclusions

To increase the productivity in the context of increasing the efficiency of the production process of plastic and aluminum windows and doors, as a whole, there was processed draft of the measures to optimize material flow in software program TX Plant Simulation.

The optimal solution is related to the introduction of a new production line. This software was helpful in the process of design and appreciation by comparison with

Peter Trebuňa; Miriam Pekarčíková; Andrea Petríková; Radko Popovič; Marek Kliment

the default state. Chosen production facilities were allocated to the production hall of the company in area of Tx Plant Simulation. The principal value of the simulation is that the proposed solutions allow you to check prior to their implementation and to identify possible errors. Direct intervention into the production process would initiate significant expenses.

Evaluation of investment measures is an important part of a comprehensive process of optimization. This is a quantification of economic indicators which help to assess the proposed solutions and prepare a basis for decisionmaking in relation to planned changes in the company. The case study focused specifically to quantify labor costs, net present value, index, present value, discounted payback period, and determining whether the investment would increase the market value of the company. Based on the above facts it can be concluded that the proposed measures would certainly contribute to the optimization of material flow and increase the productivity of the enterprise.

### Acknowledgement

This article was created by implementation of the grant project VEGA 1/0708/16 "Development of a new research methods for simulation, assessment, evaluation and quantification of advanced methods of production".

## References

- [1] DLOUHÝ, Martin et al.: Simulace podnikových procesu. Brno: Computer Press. 2007. (Original in Czech)
- [2] KVIATKOVÁ, S.: Optimalizácia materiálového toku pri výrobe vybraného produktu, DP, SjF TU of Kosice, Kosice, 2012. (Original in Slovak)
- [3] EDL, M. KUDRNA, J.: Metody průmyslového inženýrství. 1<sup>st</sup> edition, Plzeň, Smart Motion, s.r.o., 2013. (Original in Czech)
- [4] EDL, M., LERHER, T., ROSI, B.: Energy efficiency model for the mini-load automated storage and retrieval systems, *International Journal of Advanced Manufacturing Technology*, Jan 2014, Vol. 70 Issue 1-4, p. 97, 2014.
- [5] TUČEK, D., TUČKOVÁ, Z., ZÁMEČNÍK, R.: Business Process Management with Software Support, In Proceedings of the 13th International-Business-Information-Management-Association Conference: Knowledge Management and Innovation in Advancing Economies Analyses & Solutions, pp. 1060-1073, Norristown: IBIMA, 2009.
- [6] STRAKA, M.: Diskrétna a spojitá simulácia v simulačnom jazyku EXTEND, Košice, TU F BERG, Edičné stredisko/AMS, p. 102, 2007, On line: http://people.tuke.sk/martin.straka/web/web\_downloa d/Simulation\_scriptum\_2.pdf (Original in Slovak)

- [7] MALINDŽÁK, D. a kol.: Modelovanie a simulácia v logistike /teória modelovania a simulácie/, Košice, TU-BERG, p. 181, 2009. (Original in Slovak)
- [8] PAHOLOK, I.: Simulácia ako vedecká metóda. E-LOGOS. Electronic Journal for Philosophy. 2008. (Original in Slovak)
- [9] STRAKA, M.: Simulácia diskrétnych systémov a simulačné jazyky. Košice: Editačné stredisko / AMS, Fakulta BERG. 2005. (Original in Slovak)
- [10] SANIUK, S., SANIUK, A.: Rapid prototyping of constraint-based production flows in outsourcing, *Advanced Materials Research*, Vol. 44-46, pp. 355-360., 2008.
- [11] SANIUK, S., SANIUK, A., LENORT, R., SAMOLEJOVA, A.: Formation and planning of virtual production networks in metallurgical clusters, *Metalurgija*, Vol. 53 No. 4, pp. 725-727, 2014.
- [12] TREBUŇA, P., KLIMENT, M., MARKOVIČ, J.: PLM and its benefits and use in the management of complex business activities in the planning and optimization of production activities, *Manažment podnikov*. Vol. 3, Issue 2, p. 53-56, 2013.
- [13] BOŽEK, P., KŇAŽÍK, M.: The new methodology for simulation of the production system, Izhevsk: Publishing House of Kalashnikov ISTU, In: EQ-2014: In the framework of International Forum "Education Quality – 2014", Izhevsk, p. 245-248, 2014.

### **Review process**

Single-blind peer reviewed process by two reviewers.



MONTE CARLO SIMULATION FOR ANOVA

Gabriela Ižaríková

Received: 13 June 2016 Accepted: 17 July 2016

Volume: 2 2016 Issue: 2 Pages: 11-15 ISSN 1339-9640

# MONTE CARLO SIMULATION FOR ANOVA

# Gabriela Ižaríková

TU of Košice, Faculty SjF, Institute of Special Technical Sciences, Department of Applied Mathematics and Informatics, Letná 9, 042 00 Košice, gabriela.izarikova@tuke.sk

Keywords: One-way ANOVA, simulation, Monte Carlo method

Abstract: The article we will present Monte Carlo simulation for assessing consequences of data non assumption. Analysis of variance (ANOVA) ) is used to determine whether there are any significant differences between the means of three or more independent (unrelated) groups. Fundamental assumption for ANOVA is that the independent variable is normaly distributed and groups with equal variances. Monte Carlo simulation we observed Type I. error rate of analysis of variance.

#### 1 Introduction

Using quantitative mathematical or statistical model looking for the best optimal solution. In practice it is often unrealistic to find an optimal solution, for example, there are used the basic conditions of the methods. It is possible to use simulating models to solve these situations. Simulating real problems is one of the most frequently used approach that facilitates decision-making. The simulation model generally shows a system modeled mathematical formulations and logical using relationships. In the model we distinguish between a random input to control, that is transformed to output model. For the simulation experiment in the beginning you select controlled access and random (stochastic) inputs are randomly generated.

Simulations are among the quantitative tools that can be used for decision support. Simulation of work with a particular model is an experiment with the model. It is a subset of simulation modeling allows broaden the scope of the investigation and of the specific model types. Monte Carlo simulation method is known that uses a large number of randomly generated samples from the probability distribution that is used for computer simulation solutions to various managerial problems from mathematics, physics, financing, design, sales, human resources, psychology and other [1], [2].

In statistical theory, we meet two basic types of methods: parametric and nonparametric. Parametric methods (tests) are characterized in that they comply with certain assumptions. If you fulfill the requirements of the methods, such as processed data come from a normal distribution, statistical methods offer an effective and valid estimates of the probability distribution of statistics [3]. When the theoretical assumptions do not examine data, then the validity of the statistics reliable estimates of the probability distribution is uncertain. In such situations, it is possible to use Monte Carlo simulations [4], [5]. This method favors empirical estimates statistics probability distribution file prior theoretical expectations on these figures. The essence of Monte Carlo method is that it

generates numerous scenarios studied a random file. Using Monte Carlo simulation can demonstrate how to approach the theoretical results. In this paper, the Monte Carlo method applied to a situation where the assumptions are not met statistical methods, namely analysis of variance (ANOVA).

Monte Carlo method comprises the following steps:

- Determine the objective of the simulation.  $\geq$
- Propose appropriate methods of Monte Carlo.
- $\geq$ On the basis of concrete statistics randomly generated data.
- Implement quantitative methods.
- $\triangleright$ Quantify the necessary statistics.
- ⊳ Simulation contrary (eg. 100 to 1 000,000 times).
- ⊳ Analysis of statistics found.
- $\triangleright$ Assess the results obtained by the methods of Monte Carlo.

#### **One-way ANOVA** 2

The One-way ANOVA (analysis of variance) is used to determine whether there are any significant differences between the means of three or more independent (unrelated) groups. The one-way ANOVA compares the means between the groups you are interested in and determines whether any of those means are significantly different from each other [6]. Specifically, it tests the null hypothesis (1):

H<sub>0</sub>: 
$$\mu_1 = \mu_2 = \mu_3 = \cdots + \mu_k$$
 (1)  
and then H<sub>1</sub>: non H<sub>0</sub>

where  $\mu$  - group mean and k - number of groups. If, however, the one-way ANOVA returns a significant result, we accept the alternative hypothesis (H<sub>1</sub>), which is that there are at least two group means that are significantly different from each other. Its aim is to detect whether any differences between the means for these files are statistically significant or only incidental. Analysis of variance was trying to figure out which of quantitative or



**MONTE CARLO SIMULATION FOR ANOVA** Gabriela Ižaríková

qualitative factors significantly influence the monitored variables.

The basic assumptions for the use of analysis of variance include:

- Independence of observations the individual selections are independent of each other.
- Normality of sampling distribution the samples come from a core set of normal distribution.
- Homogeneity of variance (homoscedasticity) equal variances.

*Number of factors examined by analysis of variance divided on:* 

- One-way analysis of variance if the observed effect of one factor.
- Multi-factorial analysis of variance for the monitoring of the impact of several factors. According to distinguish the range of sample:
- Balanced model if the coverage is the same sample.
- > Unbalanced model- if different range of sample.

Random selection of independence is considered logically and ensure the appropriate selection of files. To verify in practice the second and third condition. Whether the results are valid in ANOVA failing these checked by using the Monte Carlo simulation, in which will be monitored type I error by One-way ANOVA (p-value).

## 2.1 Various alternative for simulation by Monte Carlo methods

Specifically, in this paper it is to test the hypothesis of conformity means of three groups:

H<sub>0</sub>: 
$$\mu_1 = \mu_2 = \mu_3 = 100$$

Compared to the alternative hypothesis that the at least two diameters are equal. The simulation method Monte Carlo we will consider all alternatives that may arise, this means meeting respectively. failure to comply with terms and conditions of normality data homogeneity of each group. Consider the following alternatives: (Table 1)

- The data come from a normal distribution with means (averagea)  $\mu = 10$ .
- The data come from the division that has skewness  $\gamma_3=1.15$  and kurtosis  $\gamma_4=2$ .
- Where equal variances we suppose  $\sigma_1^2 = \sigma_2^2 = \sigma_3^2 = 25 \,.$
- In case of different variances we suppose  $\sigma_1^2 = 4, \sigma_2^2 = 25, \sigma_3^2 = 49.$
- Assume that the individual files have the same number of observations, for example, the twenty.

Probability density graphs for all possible alternatives are on the Figure 1. Normal distribution is bell-shaped, which takes a maximum at  $x=\mu$ . The hill is steepened when variances are smaller.

The assumptions of normality can be tested e.g. Shapiro-Wilk test. The Shapiro–Wilk test utilizes the null hypothesis principle to check whether a sample  $x_1, ..., x_n$  came from a normally distributed population. Result of test is *p*-value, if  $p < \alpha$  ( $\alpha = 0,05$ ) and the null hypothesis is rejected on the significance level is 0.05. Test results for the various alternatives are in Table 2. Alternatives C and D does not satisfy the condition of normality.

The equal of variances basic set can be determined by Bartlett's test, it's a universal test that can be used for assessing the homogeneity of variances, but is relatively weak and quite sensitive to the violation of normality files, which can be a problem for files with a small number of observations. If the frequency of all choose the same used to test Cochrane test or Hartley test. The most commonly used test for homogeneity of variance test is Leveneov test, which we test the homogeneity of the various alternatives (Table 3). Alternatives B and D does not satisfy the condition of homoscedasticity.

Alternatives	Normal distribution	Normality	Homogeneity of variance
Α	$N_1(10,25)$ $N_2(10,25)$ $N_3(10,25)$	yes	yes
В	$N_1(10, 4)$ $N_2(10, 25)$ $N_3(10, 49)$	yes	no
С	$N_1(\mu, 25)$ $N_2(\mu, 25)$ $N_3(\mu, 25)$ $\gamma_3 = 1.15 \gamma_4 = 2$	no	yes
D	$N_{1}(\mu, 4) \qquad N_{2}(1 \mu, 25) \qquad N_{3}(\mu, 49)$ $\gamma_{3} = 1.15 \gamma_{4} = 2$	no	no

Table.1 Alternatives for One-way ANOVA - Monte Carlo simulation

### 2.2 Generating random numbers

Data should be generated for the Monte Carlo simulation. To create simulation models can also use MS Excel and its enhancements: Risk Solver, @Risk, Risk Analyzer, Monte Carlo. In Microsoft Excel for generating random numbers, you can use the command *RAND* (), we

get a random number with uniform distribution in the interval (0,1), or you can use the *"Random Number Generation"* the Data Analysis ToolPak on the Tools menu. We get a random number  $X \sim N(\mu, \sigma^2)$  with a given means and standard deviation. The program STATISTICA for generating random numbers, you can



Gabriela Ižaríková

use the "*Rnd* (x)", which generates a random number of interval (0, x), or the "*RndNormal* (x)', which calculates.

The number from a normal distribution with a means 0 and standard deviation x. Example of generating random number is in Figure 2.



Figure 1 The graph probability density of the alternatives

Table 2 Shapiro-Wilk test							
Alternatives	SW-W (A=0.05) 0.90499997	p-value	Result (A=0.05)				
$A_1$	0.973	0.8174	$H_0$ accepted				
$\mathbf{A}_2$	0.9555	0.4587	$H_0$ accepted				
<b>A</b> 3	0.9534	0.4224	$H_0$ accepted				
<b>B</b> <sub>1</sub>	0.9309	0.1604	$H_0$ accepted				
$\mathbf{B}_2$	0.9439	0.2834	$H_0$ accepted				
<b>B</b> <sub>3</sub>	0.9127	0.0717	$H_0$ accepted				
C1	0.8074	0.0011	$H_0$ rejected				
$C_2$	0.8964	0.0354	$H_0$ rejected				
<b>C</b> 3	0.9238	0.1172	$H_0$ accepted				
$\mathbf{D}_1$	0.9503	0.3722	$H_0$ accepted				
$\mathbf{D}_2$	0.8864	0.0231	$H_0$ rejected				
$\mathbf{D}_3$	0.8349	0.0030	$H_0$ rejected				



MONTE CARLO SIMULATION FOR ANOVA

Gabriela Ižaríková

Table 3 Levenov test - testing homogeneity of variances											
Variable	Levene Test of Homogeneity of Variances (levene)										
	Marked ef	fects are	significant a	t p < .0500							
	SS	SS df MS SS df MS F p									
	Effect	Effect	Effect	Error	Error	Error					
Α	31.76869	2	15.88435	481.5002	57	8.447372	1,880389	0,161781			
В	194.5966 2 97.29828 523.8941 57 9.191124 10.58611 0.000123										
С	8.288350	2	4.144175	575.9281	57	10.1040	0.410152	0.665492			
D	116.0580	2	58.02901	363.2120	57	6.372414	9.106674	0.000370			

Since we need to generate value from  $N(\mu, \sigma^2)$  a given means and standard deviation that can be generated directly using the "Random Number Generation" (MS Excel) and enter the parameters or to perform transformations (2):

$$Y = X * \sigma + \mu \,, \tag{2}$$

where  $X \sim N(0, 1)$  and  $Y \sim N(\mu, \sigma^2)$ ,  $\mu$  is the means value and is variance.

In the case of data generation with determined skewness and kurtosis it is appropriate to use Fleishman's power of transformation methods. Fleishman's the squares polynomial transformation (3) has the form:

$$Y = a + b * X + c * X2 + d * X3,$$
(3)

where Y is the transformed variable with the desired skewness and kurtosis, and  $X \sim N(0, 1)$  and *a*, *b*, *c*, *d* are the coefficients of which are, for some pairs of skewness and kurtosis tabulated, for example, we used the values of Table 4.

ANOVA procedure was implemented for the various alternatives and tracks the probability of passing a null hypothesis. The group had of identical means and changed only valid or invalid assumptions about normality and equal variances ANOVA. This means that the null hypothesis should not be rejected. Results simulations (p-value) are in Table 5 and Table 6.



Figure 2 Generating random number

Skewness	d				
1.15	2	-0.1858204	0.9368777	0.1858204	0.0092367



10

0.2688

Gabriela Ižaríková

	Table 5 Results ANOVA – p-value											
Sim.		Α		В		С		D				
	р	-value	p-value		p-value		p-value					
1	0.9211	$H_0$ accepted	0.8347	$H_0$ accepted	0.6609	$H_0$ accepted	0.7718	$H_0$ accepted				
2	0.8001	$H_0$ accepted	0.4882	$H_0$ accepted	0.3202	$H_0$ accepted	0.8374	$H_0$ accepted				
3	0.2915	$H_0$ accepted	0.9821	$H_0$ accepted	0.9458	$H_0$ accepted	0.6719	$H_0$ accepted				
4	0.5469	$H_0$ accepted	0.7435	$H_0$ accepted	0.0237	$H_0$ rejected	0.8086	$H_0$ accepted				
5	0.6912	$H_0$ accepted	0.2623	$H_0$ accepted	0.8217	$H_0$ accepted	0.9492	$H_0$ accepted				
6	0.2072	$H_0$ accepted	0.7946	$H_0$ accepted	0.8590	$H_0$ accepted	0.8237	$H_0$ accepted				
7	0.0128	$H_0$ rejected	0.9091	$H_0$ accepted	0.8286	$H_0$ accepted	0.8537	$H_0$ accepted				
8	0.3029	$H_0$ accepted	0.7089	$H_0$ accepted	0.0213	$H_0$ rejected	0.2053	$H_0$ accepted				
9	0.7165	$H_0$ accepted	0.8639	$H_0$ accepted	0.1920	$H_0$ accepted	0.1952	$H_0$ accepted				

Table 6 Outup of simulation method Monte Carlo for

		i	n = 10		
	Normality	Equal Var	H <sub>0</sub> accepted	H0 rejected	Freq.
Α	yes	yes	9	1	10%
В	yes	no	10	0	0%
С	no	yes	8	2	20%
D	no	no	10	0	0%

For each alternative. was found the percentage of rejection of the null hypothesis at a significance level of 5%, Tab.6. In the case of meeting the assumptions of normality were refusals 10% of cases, even if the conditionality correlation variance. When normality was not met we reject the null hypothesis twice if it was met assumption of conformity variances, it means that we have committed type I error in 20% of cases. The results of the simulation study for the 100 simulations are in Table 7, which indicates that the method is sensitive to ANOVA assumption of equal variances as the normality of the data.

Table 7 Outup of simulation method Monte Carlo for n=100

	Normality	Equal Var	H <sub>0</sub> accepted	H <sub>0</sub> rejected	Freq.
Α	yes	yes	96	4	4%
B	yes	no	89	11	11%
С	no	yes	92	8	8%
D	no	no	84	16	16%

## Conclusion

The article is an example of Monte Carlo simulations for using ANOVA. It's proven to have the fulfillment of the assumptions of normality of data and correlation scattering on ANOVA results. In the event of failure of assumptions it can be used to compare mean values more than two core set of non-parametric tests, example Kruskal-Wallis test.

# Acknowledgement

 $H_0$  accepted 0.9614  $H_0$  accepted 0.8598  $H_0$  accepted 0.7428  $H_0$  accepted

This article was created by implementation of the grant project VEGA 1/0708/16 "Development of a new research methods for simulation, assessment, evaluation and quantification of advanced methods of production".

### References

- [1] FLEISHMAN, A.I.: Functions for Simulating Data by Using Fleishman's Transformation, [Online], Available: https://support.sas.com/publishing/authors/extras/65 378\_Appendix\_D\_Functions\_for\_Simulating\_Data\_ by\_Using\_Fleishmans\_Transformation.pdf [10 Apr 2016], 2016
- [2] KOČIŠKO,M.: Simulácia výrobných systémov, FVT TUKE, 2016. (Original in Slovak)
- [3] MALINDŽÁK, D. et al.: *Modelovanie a simulácia v logistike* /teória modelovania a simulácie/. Košice: TU-BERG, p. 181, 2009. (Original in Slovak)
- [4] TREBUNA, P. et al: *Modelovanie v priemyselnom inžinierstve*, TUKE, 2015. (Original in Slovak)
- [5] STRAKA, M.: Diskrétna a spojitá simulácia v simulačnom jazyku EXTEND, Košice, TU FBERG, Edičné stredisko/AMS, [Online], Available: http://people.tuke.sk/martin.straka/web/web\_downlo ad/Simulation\_scriptum\_2.pdf [10 Apr 2016], 2007. (Original in Slovak)
- [6] BOHÁCS, G., SEMRAU, K. F.: Automatic visual data collection in material flow systems and the application to simulation models, *Logistics Journal*, p. 1-7, 2012.

### **Review process**

Single-blind peer reviewed process by two reviewers.

Acta Simulatio

- International Scientific Journal about Simulation Volume: 2 2016 Issue: 2 Pages: 17-20 ISSN 1339-9640



**MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS** Sergey Ponomarev; Artem Bondarenko; Elena Averianova; Marina Spolohova

> Received: 24 June 2016 Accepted: 19 July 2016

# MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS

# **Sergey B. Ponomarev**

Izhevsk, Russia, 426000, Vorovskogo st. 148,33, Research Institute of the Federal Penitentiary Service of Russia, Moskow, Russia, 125130, Narvskaja st.,15A, Kalashnikov Izhevsk State Technical University, Izhevsk, Russia, 426000, Studencheskaja st. 7, docmedsb@yandex.ru

# Artem V. Bondarenko

Moskow, Russia, 109388, Kuchmisterova st., 18,133, Research Institute of the Federal Penitentiary Service of Russia, Moskow, Russia, 125130, Narvskaja st. 15A, artibond@mail.ru

# Elena L. Averianova

Pskov, Russia, 180000, Lenin st., 22,45, Research Institute of the Federal Penitentiary Service of Russia, Moskow, Russia, , 125130, Narvskaja st. 15A, averyanova8@mail.ru

# Marina A. Spolohova

Izhevsk, Russia, 426000, Kalashnikov st., 101, 457, Kalashnikov Izhevsk State Technical University, Izhevsk, Russia, 426000, Studencheskaja st. 7, marisa\_90@list.ru

*Keywords:* mathematical modeling, linear regression model, human immunodeficiency virus, acquired immunodeficiency syndrome.

*Abstract:* The article features a method developed for forecasting the development of AIDS in HIV-infected patients. Mathematical model is drafted and probability of the disease determined per stages. Method helps in the diagnosis and treatment of HIV infection and can be used in daily medical practice. Currently, the method is going through patent registration procedures (registration number of the application RU 2015123255 dated 18 June 2015). It is expected that the use of this technique will help penitentiary doctors take appropriate therapeutic measures for patients with high prognostic index on time thus preventing implementation of a negative prediction.

# 1 Introduction

A majority of people with HIV employed in the UK report that HIV has no impact on their working life at present, according to research conducted by City University on behalf of the National AIDS Trust. Although most of those who disclosed their HIV status at work had had a generally positive reaction, stigma and discrimination create more problems at work than illhealth. However, only a minority of people with HIV are fully aware of the provisions of the Disability Discrimination Act.

Although the quantitative findings only relate to gay and bisexual men living with HIV, the researchers also conducted focus group discussions with a more diverse mix of people with HIV, and they say that the points of similarity between the black Africans and the gay men were striking.

Previous research in other countries has identified barriers to employment for people with HIV, and levels of employment tend to be lower than in the general population. However improved treatments mean that more people with HIV are able to remain in employment.

While the experiences of people working in the UK remain under-researched, a previous study among HIV clinic attendees in East London did identify that white gay men were more likely to be in employment than heterosexual black African men and women. More parttime working and financial problems were reported by Africans. White gay men reported higher rates of disclosure to employers than either black African heterosexuals or gay men from minority ethnic backgrounds.

The new research used focus groups to establish key themes. Three groups were held with black African heterosexuals, and two groups with gay and bisexual men (38 participants in total). Then, an online questionnaire was conducted with gay and bisexual men using the Gaydar website in order to quantify the insights of the focus groups. The researchers regret that there is no equivalent website which could be used to recruit a large convenience sample of black African people with HIV, and that other recruitment methods would have been too costly.

A total of 1830 HIV-positive gay male respondents took part in the online survey. (Moreover, some comparisons are made between these men and over 6000 HIV-negative gay men who also completed the survey.)

It's important to note that the research only included people with current employment, and the experiences of those who are no longer working are likely to be different.Twenty-five years ago the world received news about the previously unknown virus that destroys the human immune system - HIV (human immunodeficiency virus). This virus infection inevitably leads to incurable,



**MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS** Sergey Ponomarev; Artem Bondarenko; Elena Averianova; Marina Spolohova

fatal disease – AIDS and then death. In a short period of time in human history the virus carried thirty millions lives away and so far more than 80 millions people in the world live with HIV.

Over half the respondents (58%) said that living with HIV had no impact on their working life at the moment.

Of those who reported an impact, the most common responses were to report feeling very tired (20%) and feeling very stressed or anxious (13%). One in ten (11%) said that side-effects from treatment were having an impact on their work.

Seventy per cent of gay men living with HIV had taken no HIV-related sickness days in the last 12 months, and took no more sick days than HIV-negative men. Only a third had made any changes to their working lives because of their HIV status, with the most common change being alterations to working hours.

On the other hand, initial diagnosis of HIV was a time when many respondents did report an impact on their working life. Forty-two per cent reported stress or anxiety, 32% needed some time off, and 28% were very tired. However, it is important to note that almost a third of respondents said that their initial diagnosis had no impact on their working life. There was some suggestion from focus group discussions that starting or changing medication was another 'flash point' when HIV had an impact on their working lives [1], [2].

## 2 Solution design

By the number of HIV infection occurrences and the spreading velocity of infection Russia is ranked in the world ahead of countries such as China, India, Ethiopia and Nigeria etc. 60 percents of people living with the HIV-infection are concentrated in 10 Russian regions. 80 percents of HIV-infected people in Russia are young people between 18 and 30 years. More and more women are beeing involved in the epidemic process, a growing number of children are beeing born by infected mothers.

In the last few decades we can see the rapid spread of drug addiction in the Russian society, and reduction in the quality of life in Russia associated with the epidemic of HIV and TB. That led to the increase in the proportion of people suffering from co-infected (HIV + TB) [3], [4], [5]. This problem is very actual for penal system, where is a high concentration of these patients. Thus, over the last 20 years the number of HIV-infected people in prison have increased more than in 800 times. Nowadays about 56 thousand people with HIV -infection and about 30 thousand TB patients are contained in Russian prisons [5].

The dynamisc of number of patients with HIV in Russian prisons is shown in figure 1.



Figure 1. The dynamisc of number of patients with HIV in Russian prisons

It is widely known that the prediction of the final stage of HIV infection - Acquired Immune Deficiency Syndrome (AIDS) is not developed enough [6], [7] due to a large number of parameters that affect the course of HIV infection [8], [9], [10], [11]. This is especially significant for a prison, where there are many specific factors that might speed up the time of AIDS [12]. It is known that the combination of HIV and TB worsens the prognosis of the disease. The action of penitentiary factors in Russian prisons also leads to the progression of the disease and the onset of end-stage of HIV infection.

It is known that there are a number of indicators by which the medical men can determinate the risk of AIDS development in patient with HIV infection.

The aim of the study was to get a method of forecasting the development of AIDS in HIV-infected patients by means of mathematical modeling.

In accordance with the concept of developing the forecast [13], 49 covariates were initially considered as input variables (xi) - the leading characteristics of the health status of HIV-infected people held in places of detention in the Russian Federation. Variable (y) is taken as a resulting factor reflecting the dynamics of the disease within a year upon completion of the study. The stable condition of a patient was taken as "1", and number "5" was to indicate the rapid development of AIDS, followed by lethal termination.

Statistical database on which the simulation was conducted according to function y = f(xi) included 30 observations. The review team included 37 observations.

Construction of a mathematical model in which factors xi providing significant impact on the value of y were selected, was carried out by the procedure of stepped inclusion of the factor in the regression linear model y = f(xi). As a result, 4 of 49 variables were selected which make the largest contribution to the explanation of the variations in the dependent variable.





MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS Sergey Ponomarev; Artem Bondarenko; Elena Averianova; Marina Spolohova

# **3** Mathematical formula

Mathematical formula takes into account the formalization of the patient's complaints (the presence of cough, muscle pain, loss of appetite and other results of medical tests). In addition, the border of liver according to the mid-clavicular line based on the M.G.Kurlov classical technique (1927) was further measured by percussion [14].

The method of least squares has determined coefficients of the linear regression of the following (1) form:

$$y = \alpha_1 \cdot t_1 + \alpha_2 \cdot t_2 + \alpha_3 \cdot t_3 + \alpha_4 \cdot t_4 + \alpha_5 \cdot t_5 + \alpha_6 \cdot t_6 + \alpha_7 \cdot t_7 + e, \quad (1)$$
  
where v is integral index,

 $\alpha_1, \alpha_2, \alpha_3, \alpha_4$  · is weighting coefficients,

 $\cdot t_1, t_2, t_3, t_4$  are measurable parameters, *e* are residues.

The parameters of medical examination (such as the presence and stage of concomitant tuberculosis, severity of myalgia, increasing the degree of lymph nodes, presence of cough, liver size by Kurlov, laboratory tests, etc) as predictors in multiple regression formula used.

Calculations show that patients who have cough, are subject to AIDS progress risk by 0.352 units. Patients who have myalgia (muscle pain), are subject to AIDS progress risk by 69.7%, patients who have enlarged lymphnodes are subject to AIDS progress risk by 0.764 units. Stages of tuberculosis development also aggravate the situation of the patient.

The reseaches show that in case when the value of y was less than 3 units low risk of developing AIDS was predicted within the nearest year. While at a value within  $3 \le 4$  units the average risk of developing AIDS is determined within the nearest year, at a y value of more than 4 units a higher risk of developing AIDS within the nearest year of observation was predicted.

To assess the adequacy of the constructed model the coefficient of determination  $R^2$  (the ratio of the explained dispersion to the total one) (2) (3) was used:

$$R^2 = \frac{RSS}{TSS} \tag{2}$$

wherein 
$$RSS = \sum_{t=1}^{T} (y_t^{mod} - \overline{y})^2$$
,

$$TSS = \sum_{t=1}^{T} (y_t - \overline{y})^2$$
(3)

If  $R^2 = 0$  then the regression does not improve  $y^{mod}$ 

the quality of prediction  $y_t^{mod}$  as compared with the trivial prediction  $\overline{y}$ . If  $R^2 = 1$ , they say it means the

exact fit of the model, i.e., all observation points comply with the regression equation.

# 4 Known connection

The coefficient of determination R2 = 0,783 shows that 4 of the variable estimates 78.3% of the variation of the result.

To determine the significance of the coefficients of the regression model, hence the importance of the entire model, the Fisher statistics (4) was used F:

$$F = \frac{R^2}{1 - R^2} \cdot \frac{n - k}{k - 1} , \qquad (4)$$

where n is the number of observations,

k is the number of estimated parameters.

The main and alternative hypotheses are advanced (5), (6):

$$H_{0}: \boldsymbol{\beta}_{i} = 0 ; \qquad (5)$$

$$H_1: \boldsymbol{\beta}_i \neq 0$$
 (6)

When the main hypothesis statistics F has Fisher distribution with (k-1, n-k) degrees of freedom. Value F is compared with the tabulated value  $F_{\alpha}(k-1, n-k)_{\text{at}}$  significance level  $\alpha$ . If  $F < F_{tab}(k-1, n-k)$ , then the main hypothesis that regression coefficients are equal to zero is accepted. If  $F > F_{tab}(k-1, n-k)$ , then the main hypothesis is rejected in favor of an alternative.

For the estimated model Fisher test was 3.17. The probability to randomly get such a value of F-test does not exceed the acceptable level of significance of 5%. Therefore, the resulting value of the Fisher criterion confirms the statistical significance of the model.

Additionally, the average relative error of approximation has been calculated by (7) the formula:

$$\overline{\delta} = \frac{1}{N} \sum_{t=1}^{N} \frac{\left| y - y^{\text{mod}} \right|}{y} \cdot 100\%$$
(7)

Where N is the number of observations;  $y^{\text{mod}}$  is the model value of the index.

The average relative error of approximation was 8.2%. When checking the model on a test subgroup with HIV infection, acceptable values of correlation coefficient r = 0,58 between predicted and actual values of the prognostic index were observed.

Approximation error graph is shown in Figure 2.



**MATHEMATICAL METHOD FOR FORECASTING AIDS PROGRESSION IN HIV-INFECTED PATIENTS** Sergey Ponomarev; Artem Bondarenko; Elena Averianova; Marina Spolohova



# Conclusions

In conclusion, in the course of research a methodology was obtained which, with reasonable accuracy, can indicate risk of AIDS development in HIV-infected patients who are serving their sentence of imprisonment in correctional facilities of the Federal Penitentiary Service of the Russian Federation. Currently, the method is going through patent registration procedures (registration number of the application RU 2015123255 dated 18 June 2015). It is expected that the use of this technique will help penitentiary doctors take appropriate therapeutic measures for patients with high prognostic index on time thus preventing implementation of a negative prediction. Mathematic method helps in the diagnosis and treatment of HIV infection and can be used in daily medical practice in prisons.

The advantages of the method are simplicity of definition, low cost, convenience, high accuracy, absence of threat to the patient health. Also there is no need for expensive equipment and the possibility of determining the risk of AIDS in HIV infected patient is high.

# References

- [1] WORKING WITH HIV: A summary of NAT's HIV employment research, National AIDS Trust, 2009.
- [2] DOUGLAS N. I.: Just get on with it... A study of the employment experiences of gay and bisexual men and black African men and women living with HIV in the UK. National AIDS Trust, 2009.
- [3] DOS SANTOS R.P., DEUTSCHENDORF C., SCHEID K., ZUBARAN GOLDANI L.: In-Hospital Mortality of Disseminated Tuberculosis in Patients Infected with the Human Immunodeficiency Virus. -Clin Dev Immunol, p. 120-278, 2011.
- [4] PAYAM N., LEAH C. G., RUDOY I.: Treatment Outcomes of Patients with HIV and Tuberculosis, *Amer. J. Respir. Crit. Care Med.*, Vol. 175. p. 1199– 1206, 2007.
- [5] AVERIANOVA E.L., GOROCHOV M.M., PONOMAREV S.B., PONOMAREVA A.S.: The problems of socially significant diseases information

monitoring, Pskov, p. 115, 2015. (Original in Russian)

- [6] NAUMOV O.U., LUZIN P.M.: The methodological approach to forecasting the incidence of HIV infection in the Perm region, Topical issues of HIV on Urale, Ekaterinburg, p. 45-48, 1995. (Original in Russian)
- [7] TROTSENKO O.E., STAROSTINA I.S., BOGACH V.V.: Clinical and laboratory criteria of HIV disease progression among individuals in penitentiary institutions, Khabarovsk, p. 49, 2004. (Original in Russian)
- [8] DENISENKO V.B., SIMOVANYAN E.M.: *Method* for predicting types of the course of HIV infection with children, Patent for the invention RU 2444299 dated 10.03.2012. (Original in Russian)
- [9] SIMOVANYAN E.M., DENISENKO V.B.: *Method* of predicting variants of the course of HIV infection with children. Patent for the invention RU 2454941 from 10.07.2012. (Original in Russian)
- [10]AMBALOV U.M., SIZYAKINA L.P., PEREPECHAI S.D.: A method of prediction of the rapid progression of disease in patients with HIV infection, Patent for invention RU 2306566 from 20.09.2007. (Original in Russian)
- [11]TABAKOV V.V., NIKITIN V.V.: A method of predicting the level of HIV infection in the region, Patent for invention RU 2297787 dated 27.04.2007. (Original in Russian)
- [12]ZHEVAGINA N.A., ZHELEZNYAKOVA L.A.: Peculiarities of co-infection of HIV and tuberculosis with patients in the penitentiary system, Penitentiary Medicine: history, current state and development prospects, Proceedings of the conference dedicated to the 10<sup>th</sup> anniversary of the Izhevsk branch of the PKU Research Institute of the Federal Penitentiary Service of Russia (September 5, 2015), p. 88-90, 2015. (Original in Russian)
- [13]PONOMARIEV S.B., LESZCZYNSKI L.A., RUSYAK I.G.: *Essays of prediction in cardiology*, Izhevsk, p. 192, 2000. (Original in Russian)
- [14]KURILOV M.G.: *Clinical lectures on domestic diseases*, Tomsk, p. 201. (Original in Russian)

## **Review process**

Single-blind peer reviewed process by two reviewers.





ABOUT/STATEMENT

# JOURNAL STATEMENT

Journal name:	Acta Simulatio
Abbreviated key title:	Acta Simul
Journal title initials:	AS
Journal doi:	10.22306/asim
ISSN:	1339-9640
Start year:	2015
The first publishing:	March 2015
Issue publishing:	Quarterly
Publishing form:	On-line electronic publishing
Availability of articles:	Open Access Journal
Journal license:	CC BY-NC
Publication ethics:	COPE, ELSEVIER Publishing Ethics
Plagiarism check:	Worldwide originality control system
Peer review process:	Single-blind review at least two reviewers
Language:	English
Journal e-mail:	info@actasimulatio.eu

The journal focuses mainly on the original and new, interesting, high-quality, theoretical, practical and application-oriented contributions to the field of science and research as well as to pedagogy and education in the area of simulation.

Publisher:	4S go, s.r.o.
Address:	Semsa 24, 044 21 Semsa, Slovak Republic, EU
Phone:	+421 948 366 110
Publisher e-mail:	info@4sgo.eu

# Responsibility for the content of a manuscript rests upon the authors and not upon the editors or the publisher.